750II SENSOR SELECTION GUIDE

Conductivity/TDS, and Resistivity Monitor/controllers

FEATURES WITH T-FITT	ING (BY CUSTOMER)	WSEATION	SUBMERS	A FLOW THE.	COWANNER (*COWANNER	MEDUM RAW	10 HANG!	MAY PRESSION FRANCES	Tey Estudies
CS10 CS10LS 316SS TEFLON®*		3/4" NPT STD • 1/2" NPT OPT	•		•			100 psi/6,9 bar at 100°C/212°F	High Purity Water
CS40 CS40HT 316SS TEFLON®*	Shown w/optional wel-tap valve & junction box	3/4" NPT 1" NPT VALVE	•	•	•	•	•	100 psi/6,9 bar at 150°C/302°F 250 psi/17,2 bar at 205°C/401°F (HT OPTION)	Valve Insertable Wide Range of Measurement
CS41 CS41HT 316SS TEFLON®*		3/4" NPT	•		•	•		100 psi/6,9 bar at 150°C/302°F 250 psi/17,2 bar at 205°C/401°F (HT OPTION) 400 psi/27,6 bar at 100°C/212°F	Boiler & Condensate Service
CS50 316SS CPVC		1" NPT	•		•	•		100 psi/6,9 bar at 95°C/203°F	Low Cost
CS51 CS51LC CS51LS CS51R 316SS, TEFLON®*		3/4" NPT STD 1/2" NPT OPT	•	•	•	•		100 psi/6,9 bar at 100°C/212°F	Low Cost Small Size
CS52 316SS CPVC/ TEFLON®*/ KYNAR®**		3/4" NPT	•				•	100 psi/6,9 bar at 95°C/203°F	High Range Low Cost
CS60 316SS TEFLON®*/ KYNAR®**		1" NPT	•		•	•		100 psi/6,9 bar at 120°C/248°F	Excellent Chemical Resistance
CSA CSATC CSAR 316SS ABS PLASTIC		3/4" NPT				•		75 psi/5,2 bar at 60°C/140°F	Extremely Low Cost
Sanitec Fitting Option All CS10 & CS51 MODELS	316SS-TEFLON®*	MULTIPLE SIZES AVAILABLE		•	•	•		100 psi/6,9 bar at 120°C/248°F	Sanitec Fitting excellent for sanitary applications

2450 Impala Drive Carlsbad, CA 92010-7226 USA Tel: 760-438-2021

Fax: 800-869-7668 / 760-931-9189 www.myronl.com

Built On Trust. Founded in 1957, the Myron L Company is one of the world's leading manufacturers of water quality instruments. Because of our commitment to product improvement, changes in design and specifications are possible. You have our assurance any changes will be guided by our product philosophy: accuracy, reliability, and simplicity.

> **Water Quality Instrumentation** Accuracy • Reliability • Simplicity

