MODEL

MULTI-PARAMETER MONITOR/CONTROLLER

DESCRIPTION

MONITOR/CONTROLLERS

NOVEMBER 1, 2019 PRICE

MODEL	<u>BECOM TION</u>	IIIOL
900M-1C	Monitor/Controller with 1 Relay and 1 Alarm	
900M-3C	Monitor/Controller with 3 Relays, 2 Alarms and 4-20 mA Output	\$2446.00
	ACCESSORIES	
Power Supply		
PWRADAPT	900 Series Power Supply, Input: 100-240 VAC*, Output: 24 VAC, 1.7 A	
	*NOTE: Power cord, included, has a voltage rating of 125 VAC, 10 A	\$120.00
PCO9	Power Cord, for use with 900 Series Power Supply	
	NEMA 5-15P to IEC 320-C13, Voltage Rating: 125 VAC, Current Rating: 10 A	\$16.00
FB9	Ferrite, 310 Ohm, Hinged, 6.6 mm, package of 2	\$11.00
Misc.		
	0	400400
9CMO	Control Module, upgrades a 900M-1C to a 900M-3C	
024-1	1" NPT 24 VAC Solenoid Valve	
PMB9	Panel Mounting Bracket (with screw)	\$8.50
Alarms		
PAO	Piezo Electric Alarm, 80dB, Panel Mount	\$56.50
RA	Remote Alarm™	
RAH	Remote Alarm Harness, connector w/12" 2 conductor wire. For use w/ RA or PAO	
RAW200	Wire, 200 feet/61 meters for Remote Alarm or Piezo Electric Alarm	
		φο2.50
Mounting Brac	ket Kits	
9MBAPC	Mounting Bracket, Adapter for 700 Series Cutout, Aluminum, Powder Coat, Black	\$43.50
9MBHPC	Mounting Bracket, Horizontal, Aluminum, Powder Coat, Black	
9MBVPC	Mounting Bracket, Vertical, Aluminum, Powder Coat, Black	\$100.00
	SENSORS	
	<u>SENSONS</u>	
Conductivity/T	DS/Salinity (w/1k RTD)	
CS951	Conductivity/TDS, 3/4" NPT, 0-20,000 µS/ppm, 1.0 cell constant, 10 ft./3-meter cable	\$293.00
CS951LS	Conductivity/TDS, long style, 3/4" NPT, 0-20,000 µS/ppm, 1.0 cell constant, 10 ft./3-meter cable	
CS952	Conductivity/TDS/Salinity, 3/4" NPT, >20,000 µS/ppm, 10.0 cell constant, 10 ft./3-meter cable	
D		
Resistivity (w/1	•	
CS910	Resistivity, 34 " NPT, 10 k Ω -20 M Ω , 0.05 cell constant, 10 ft./3-meter cable	
CS910LS	Resistivity, long style, 34 " NPT, $10~k\Omega$ - $20~M\Omega$, $0.05~cell$ constant, $10~ft./3$ -meter cable	\$420.00
pH, Pre-Amplifi	ied (w/1k RTD)	
P92	pH, ½" NPT, bulb tip, pellon junction, 10 ft./3-meter cable	<u></u>
P94 P94PE	pH, ¾" NPT, bulb tip, pellon junction, 10 ft./3-meter cablepH, ¾" NPT, hemi tip, polyethylene (PE) junction, 10 ft./3-meter cable	
P94FPE P94FPE	pH, 34" NPT, flat tip, polyethylene (PE) junction, 10 ft./3-meter cablepH, 34" NPT, flat tip, polyethylene (PE) junction, 10 ft./3-meter cable	
1 34 □□□	pri, 74 ivi i, nat tip, polyethylene (FE) junction, 10 it./5-meter cable	\$ 4 50.50
ORP/REDOX, P	Pre-Amplified	
O92	ORP, ½" NPT, extended tip, pellon junction, 10 ft./3-meter cable	\$371.00
O94	ORP, 3/4" NPT, extended tip, pellon junction, 10 ft./3-meter cable	
	· · · · · · · · · · · · · · · · · · ·	

TERMS AND CONDITIONS (Additional information upon request) All special order items are non-returnable and non-refundable.

Minimum order \$25.00. All prices are US dollars and are F.O.B. Carlsbad, CA.

Terms: 1% 10 days, net 30 days on approved credit.

Credit Cards accepted: Visa, MasterCard American Express, and Discover

Because of our policy of continuous product improvement, the Myron L® Company reserves the right to make changes in design, specifications, and prices without notice.

2450 Impala Drive Carlsbad, CA 92010-7226 USA

Tel: +1-760-438-2021

Fax: +1-800-869-7668/+1-760-931-9189

www.myronl.com

Built On Trust. Founded in 1957, the Myron L® Company is one of the world's leading manufacturers of water quality instruments. Because of our commitment to product improvement, changes in design and specifications are possible. You have our assurance any changes will be guided by our product philosophy: accuracy, reliability, and simplicity.

